



OIL & GAS DEVELOPMENT COMPANY LIMITED
PROCUREMENT DEPARTMENT (LOCAL), ISLAMABAD
SCHEDULE OF REQUIREMENT

Due Date:

Material : Exploration Proof Lighting Fixtures

Tender Enquiry No: PROC-LD/PT/P&P/17369

Bid Bond Value : 90000

Attachment(if any) : YES

EVALUATION WILL BE CARRIED OUT ON FULL

Sr No	Description	Quantity	Make/Brand offered	Unit	Unit Price (PKR) Inclusive Of All Taxes Except GST	Unit Price (PKR) Inclusive of GST	Total Price (PKR) Inclusive of GST	Delivery Period Offered	deviation from Tender Spec. If Any
				Number					
1	LIGHTING FIXTURES, 2X36 WATT, EXPLOSION PROOF, Ex'd', IP65, CLASS-I, ZONE-2.	100							

Special Note:- The prospective bidders also download the master set of Tender Document

- The prospective bidders may keep in touch with OGDCL web site for downloading the clarifications/amendments (if any) issued by OGDCL.
- DELIVERY LOCATION:UCH GAS PLANT, DELIVERY PERIOD:120 DAYS AFTER ISSUANCE OF LPO, PAYMENT TERM: 100% AFTER DELIVERY.

Discount (if any) shall only be entertained on Schedule of Requirement of Bidding Document (Financial Proposal). If the discount is mentioned elsewhere in the bid, the same shall not be entertained.

TERMS & CONDITIONS FOR INDENT NO: UCH/ELEC/1116/18

- 1) THE ITEM SHOULD BE BRAND NEW AND IN ORIGINAL OEM PACKING.
- 2) STANDARD WARRANTY /GURANTTEE SHOULD BE PROVIDED.



OIL & GAS DEVELOPMENT COMPANY LIMITED

PROCUREMENT DEPARTMENT (LOCAL), ISLAMABAD

SCHEDULE OF REQUIREMENT

Mandatory Checklist

Please confirm the compliance of the following mandatory information along with the bid(s) (failing which bids(s) will not be accepted)

Documents	To be Attached with the Technical/Financial Bids	Compliance	
		Yes <input type="checkbox"/>	No <input type="checkbox"/>
Original Bid Bond	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Copy of NTN Certificate	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Copy of GST Certificate	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Confirmation that the Firm is appearing on FBR's Active Taxpayer List	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly signed and stamped Annexure-A (Un-priced)	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-B	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-D	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-L on Company's Letterhead	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly signed and stamped Annexure-M on Company's Letterhead	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly signed and stamped Annexure-N on Non-Judicial Stamp Paper duly attested by Notary Public	Technical Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-A (Priced)	Financial Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-C	Financial Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Duly filled, signed and stamped Annexure-E	Financial Bid	Yes <input type="checkbox"/>	No <input type="checkbox"/>

Generalized Specifications for 2 X 36 Watt Explosion Proof Lighting Fixture for Indent #Uch-1116

Installation:

Hazardous areas-Zone2 (Gases)

Classification:

Group II- Category 3G -3D

EXECUTION:

T85°C/T100°C/T135°C D

II 3 G Ex nA IIC T6/T5/T4 Gc II 3 D Ex tc IIIC

RULES OF COMPLIANCE:

EN 60079-0; EN 60079-15; EN 60079-31

EC Type-Examination Certificate:

IMQ 08 ATEX 008X

PROTECTION DEGREE:

IP65

AMBIENT TEMPERATURE:

-20°C ÷ +60°C

Mechanical characteristics

Body :

Glass fiber reinforced polyester resin

Diffuser:

U/V resistant polycarbonate - hinged to body

Safety closing:

Stainless steel hooks with safety device Gaskets EPDM 60
rubber suitable for high temperatures and resistant to
environments conditions

Internal reflector:

white stove enamelled sheet steel

Cable entry:

complete with 1 PVC cable gland + 1 PVC stopping plug

Electrical characteristics

Power supply:

0,98)

Dual channel electronic ballast 220÷240V AC, 50Hz ($\cos \rho \geq$

Lamp holders:

Bi-pin G13 cap

Terminals:

Suitable up to 6 sq/mm cables