





GENERAL NOTES 技术要求

1. MATERIAL OF TUBESHEET SHALL BE IN ACCORDANCE WITH ASME CODE SEC. II PART A-2010; 管板材料应符合ASME CODE SEC. II PART A-2015中的规定;
2. MINIMUM STD. LGMENTS $B \geq 4.903\text{mm}$, MINIMUM PERMISSIBLE LGMENT WIDTH OF 4% $B \geq 3.048\text{mm}$; 相邻两管孔之间的孔桥宽度 $B \geq 4.903\text{mm}$, 允许4%孔桥宽度 $B \geq 3.048\text{mm}$;
3. PERMISSIBLE TOLERANCES OF 4% TUBE HOLE IS $\phi 25.25^{+0.15}_{-0}$. 允许4%管孔公差为 $\phi 25.25^{+0.15}_{-0}$.



				
上海蓝滨石化设备有限责任公司 Shanghai Lanbin Petrochemical Equipment Co., Ltd.				
Prepared 设计		2016.07.14	图 名 DWG NAME	
Approved 批准	王 洋	2016.07.14	TUBE SHEET 管板	
			$\delta=136$	
Job No. 工 号	BU16-14			
Draw- 画 法		Material	SA-266 Gr.2N	
Phase 阶段	Construction 施工图	Page 1 of 1 第 1 张 共 1 张	Rev. 版次	0