OIL & AS DEVELOPMENT COMPANY LIMITED LOCUREMENT DEPARTMENT, ISLA, ABAD FOREIGN SECTION C

(To be completed, filled in, signed and stamped by the principal)

ANNEXURE 'A'

Material Tender Enquiry No CP OIL FOR REFRIGERATION PACKAGE

PROC-FC/CB/P&P/QP-4416/2019

Due Date

Note:

Evaluation Criteria

FULL

SCHEDIII E OF DECLIDEMENT

SCHEDULE OF REQUIREMENT							
Sr No Description	Unit	Quantity Unit Price	Total Price	Unit Price	Total Price	Deviated From	
		(FOB)	(FOB)	C & F BY SEA	C & F BY SEA	Tender Spec. If Any	
SYNTHETIC OIL, CP-1507/68 (CPI Engineering) AS PER ATTCHED TOR	DRUM	15					
	(208.2						
	LTR)						

effective from February 27, 2018. PURSUANT TO TENDER CLAUSE # 2.2, 11.4, 13 & 35.3.2, BID BOND AMOUNTING TO USD 1,130/- OR EQUIVALENT TO PAK RUPEES MUST BE SUBMITTED WITH

Note: Bidders are advised that Payment will be made as per the Foreign Procurement Payment Terms available at OGDCL Website (Tenders Tab)

- TOR: ATTACHED TOR IS INTEGRAL PART OF SOR.
- **EVALUATION CRITERIA:** FULL CONSIGNMENT WISE ON CFR BY SEA KARACHI BASIS.

THE TECHNICAL BID AND VALID FOR 150 DAYS FROM THE DATE OF OPENING OF THE BID.

TERMS AND CONDITIONS: BIDDER IS ADVISED TO CAREFULLY READ ALL THE TERMS AND CONDITIONS OF THE TENDER DOCUMENT AVAILABLE AT OGDCL WEBSITE IN THE MASTER TENDER DOCUMENT.

LUBRICANT CP OIL (CPI-1507-68)

OGDCL intends to procure CP oil (CPI-1507-68) which is currently in use in refrigeration system.

Eligibility Criteria/ TOR

- 1. Original Authority Letter for participation in the bid from OEM M/S Lubrizol must be provided with technical bid.
- 2. In case of local representative, Original Authorization Letter from principle to participate in the bid should be provided with the technical bid.
- 3. Bidder must confirm that quoted lubricant as Compression utilizing screw, and centrifugal type compressors and flow with propane in operating conditions.
- 4. Lubricant must be in original OEM Packing.
- 5. Date of Manufacturing and expiry must be mentioned on each drum.
- 6. Packing must be in drum containing 208Ltr ~210 Ltr per drum.
- 7. Lubricant must have standard OEM warranty/guarantee.
- 8. Delivery period is 90 days on C&F by Sea from date of issuance of L/C.
- 9. Bidders to submit their company profiles, experience for supply of such lubricant, coolants for engines compressors (i.e Previous Purchase Orders) along with technical bid.
- 10. Payment Terms
 - a. 70% at the time of shipment.
 - b. 30% after inspection at site.
- 11. Bidder should submit the complete compliance of TOR duly signed and stamped.

Bidder fill the table and submit with the bid with signed and stamped.

Test Procedure	ASTM Test Method	CPI®-1507-68	Bidder fill the Specs
ISO VG		68	
Density, g/mL	D4052		
20.0°C		1.135	
Flash and Fire Point,	D92		,
Flash Point °C		231	
Fire Point °C		241	
Kinematic Viscosity, cSt	D445		
40°C		68.1	(9)
100°C		10.8	
Viscosity Index	D2270	168	
Pour Point, °C	D97	-48	
Foaming Tendency, mL	D892		
Sequence I		30/0	
Sequence II		20/0	
Sequence III		70/0	
Copper Strip Corrosion	D130		
100 °C for 3 hours		1B	
Rust Test	D665		
A - Distilled Water		Pass	