

# OIL & GAS DEVELOPMENT COMPANY LIMITED

## PROCUREMENT DEPARTMENT, ISLAMABAD

### FOREIGN SECTION B

(To be completed, filled in, signed  
and stamped by the principal)

**ANNEXURE 'A'**

**Material** EPOXY PRIMER, MELT STICKS, CLOSURE PATCHES

**Tender Enquiry No** PROC-FB/CB/PE&FD-5323/2022

**Due Date**

**Evaluation Criteria** FULL

### SCHEDULE OF REQUIREMENT

Sr No	Description	Unit	Quantity	Unit Price (FOB)	Total Price (FOB)	Unit Price C & F BY SEA	Total Price C & F BY SEA	Deviated From Tender Spec. If Any
1	EPOXY PRIMER FOR 3L-PE HEAT SHRINK SLEEVES PART-A (18L-4.75GAL)	Drum (18 Ltr)	18					
2	EPOXY PRIMER FOR 3L-PE HEAT SHRINK SLEEVES PART-B (18L-4.75GAL)	Drum (18 Ltr)	6					
3	STICK MELT, 1" DIA X 12" LONG (25MM DIA X 300MM LONG) (SUITABLE ONLY FOR 3L-PE COATING)	Number	400					
4	CLOSURE PATCH FOR HEAT SHRINK SLEEVES (FOR 6" DIA PIPE)	Number	300					
5	CLOSURE PATCH FOR HEAT SHRINK SLEEVES (FOR 4" DIA PIPE)	Number	400					

**Note:**

- 1) BID VALIDITY: BID MUST BE VALID FOR 180 DAYS FROM BID OPENING DATE.
- 2) BID BOND AMOUNT: US\$ 600/- OR EQUIVALENT PKR TO BE SUBMITTED WITH TECHNICAL BID AND VALID FOR 210 DAYS.
- (3) DELIVERY PERIOD: 120 DAYS FROM L/C ESTABLISHMENT DATE.
- (4) EVALUATION CRITERIA: "FULL CONSIGNMENT WISE" ON CFR BY SEA KARACHI-PAKISTAN BASIS.
- (5) TENDER DOCUMENTS AVAILABLE ON OGDCL'S WEBSITE UNDER TAB "Tender Document for "Single Stage-One Envelope" Bidding Procedure"

**ANNEXURE-I****TOR for Closure Patch, Epoxy Primer System and Melt Stick**

Sr. No	TOR	Bidders response
1	Epoxy Primer/ Closure Patch/ Melt stick Manufacturer Authority Letter required on company letterhead, duly signed and stamped by CEO/Director concerned.	
2	Applicable standard - DIN 30670 Standard for all the three items and their application. Manufacturer & Bidder to confirm compliance to SOR and DIN 30670 Standard.	
3	Bidder must have supplied Epoxy primer, closure patch and melt sticks to Oil & Gas Exploration & Production Companies in Pakistan (Copy of Purchase Order to be submitted).	
4	Epoxy primer mixing ratio for the application of part A & B is to be provided by the OEM.	
5	Coverage Area for the application of Epoxy primer is to be provided by the OEM.	
6	OEM to confirm Epoxy primer/ Closure Patch/ Melt stick compatibility with 3-layer polyethylene sleeves of RAYCHEM (Available in OGDCL stock of 2600-3000-micron thickness). Only Raychem (or its new owner's) OR Equivalent certificate on its letterhead and stamped would be accepted for compatibility	
7	Technical brochures with details of application method on CD/ Flash drive are to be provided with the bid.	
8	Epoxy primer, melt stick, closure patch shelf life must be minimum three years under normal storage conditions. Guarantee Certificate for the shelf life (minimum 3 years) is to be provided by the manufacturer.	
9	MSDS must be provided with bid for each item.	
10	The Bidder is required to adhere to the maximum Delivery Period of 120 days on CFR Karachi by Sea basis, from the date the letter of credit (L/C) is established.	
11	The material to be supplied under the contract must be brand new (Certificate to be submitted by the bidder).	