## **Product Specification**



Lead Time: Rev: **A** 

Item: 1 Tags: Description: NPS 3 1098-EGR Service Description: Rev:

Qty: 1

Pilot Operated Regulator: Valve Size: NPS 3 Body Material: Steel Rating: CL150 End Connection: RF Flg BWE Schedule: Not App Body Flange Material: Steel NAČE: No Trim Type: Whisper Trim Material: S41600 SST Cage Material: S41600 SST Disk/Seat Material: NBR Flow Capacity: 100% Main Spring: 60 to 125 psig Actuator Size: 40 Actuator Material: Steel Diaphragm Material: NBR 17E44 Travel Indicator: Yes Pilot Type: 6352 Pilot Body Material: Aluminum Pilot Spring Range: 2 to 10 psig Pilot Trim: NBR/SST Pilot Filter: P594-1 Pilot Gain: Standard Pressure Loaded Pilot: No Restrictor: None Working Monitor Pilot Type: None Working Monitor Pilot Spring Range: None Stand-by Pilot Type: None System Control Range: Not App Pilot Tubing & Fitting Material: SST/SST Type 662 Remote Control: No Power Supply: Not App

ATEX for Regulators: No Customer Special 1098-EGR: Not App Type: 1098-EGR Main Valve Actuator: 1098 Spring Part Number: 14A6630 (Steel) Orifice/Port: 3 3/8 Travel Stop: No Pilot Spring Number: 14A9673 Pilot Spring Color: Black Pilot Spring Case Material: Aluminum Pilot Spring Case Vent Tapped: 1/4 NPT Pilot Spring Adjustment: Adjusting Screw Pilot Diaphragm Material: NBR Working Monitor Pilot Body Material: None Working Monitor Pilot Spring Case Material: None Working Monitor Pilot Spring Number: None Working Monitor Pilot Spring Color: Not App Working Monitor Pilot Diaphragm Material: Not App Working Monitor Pilot Trim: None Stand-by Pilot Spring Range: Not App Pilot Supply Regulator: No Min Diff Pressure: 6 psid Max Diff Pressure: 125 psid Max Operating Inlet Pressure: 135 psig Max Operating Outlet Pressure: 10 psig Approximate Shipping Weight(each): 130 lbs (59 kg) Supplemental Attribute: Not App Pressure: Temperature: Flowing Drop: Shutoff Drop: